

# LANCO

TentTech · DeconTech · FlexTank

## Auditorium Tents



All tent auditoriums can be extended limitlessly by 3.00 m increments. From a length of 27 m, additional wind bracings are required.

Built to last and perfect for weddings, graduations, sporting events, church functions or corporate events, our large, modular outdoor tents can accommodate your needs, your guests and events of all sizes.



Adaptive, robust and versatile



Flame retardant & UV resistant material



4 - 10 m span, customized tarpaulins possible



Aluminum frames are extremely resistant against corrosion

## Tent skin

Roof fabric and walls are made of double-sided PVC-coated polyester fabric, glossy. Flame retardant skin is in accordance with DIN 4102 B1 and M2, weight 650 g/m<sup>2</sup>. The roof is tensioned by expander, straight overhang 20 cm.

Gable triangles (divided in the middle by zipper) and side curtains in the same quality as the roof tarpaulins, alternatively side curtains with broad stripe design on the outside in white / yellow or white / blue stripes width approx. 9 cm, curtain divided in the middle of each field with a zipper, on the eaves with curtain rings, on the floor closed hemstitch to hold weight pipes.

## Applications

- ▲ Accommodation and catering
- ▲ Party and events
- ▲ Promotion agencies
- ▲ Associations & youth groups

## Setup technique



## Technical data (6 m length basic model)

	ZH 4	ZH 6	ZH 8	ZH 10
Base area	24.00 m <sup>2</sup>	36.00 m <sup>2</sup>	48.00 m <sup>2</sup>	60.00 m <sup>2</sup>
Width	4.00 m	6.00 m	8.00 m	10.00 m
Length	6.00 m	6.00 m	6.00 m	6.00 m
Ridge height	3.01 m	3.38 m	3.74 m	4.10 m
Eaves height	2.30 m	2.30 m	2.30 m	2.30 m

## Colors

The roof is always finished in white PVC, the side curtains are available in these standard colors.



## Frame

Trusses and gable poles are made of extruded 2-groove-aluminum hollow profile 84 x 48 mm. All aluminum parts are anodized and maintenance free.

Steel parts like baseplates, ridge and eaves slots are hot-dip galvanized according to DIN 50976 and extremely resistant against corrosion.

All screws are galvanized, all wind bracing ropes are plastic covered. Ground fixation with bar anchors. All tent auditoriums can be extended by 3.00 m and have a side height of 2.30 m.

## Building record book

All tent auditoriums with a base area of over 75 m<sup>2</sup> are delivered with a building record book for a fee. It includes the certified structural calculation, a report from German authorities and pages for authority checks after set-up.

For tent auditoriums of less than 75 m<sup>2</sup>, the building record book will only be supplied upon request.