CLADIS
SERVING THE RESPONSE COMMUNITY

Accommodation tent 506 G

Product Images

Short Description

Accommodation tents are spacious and comfortable, hence well suited for tent camps.

Description

Standard

Tent with entrance in the front gable (toggle closing), window 60 x 40 cm with exterior shutter in back gable, aluminium frame and accessories.

Frame

The frame system consists of anodized aluminium tubes, diameter 40 mm. The connectors and base plates are made of an aluminium alloy.

Wall thickness of 1.5 mm of the material AL Mg 4,5 Mn.
Yield strength: Rp0,2 = 330-340 N/mm2
Ultimate strength: Rm = 350-370 N/mm2

Peg, 20 mm diameter, hot-dip galvanised iron with top forged on, 700 g, 300 mm long
T-peg, galvanised iron, 300 mm long

Tent skin

LANCO tents are made of LANCO heavy- duty fabric.LANCO-heavy-duty fabric is permeable to the air, rot-resistant, water pressure proof laminated and is extremely tearproof as well as highly protective against UV-rays.

Fabric:
Twisted cotton-polyester 50%/50%Yarn

Additional Information

Application area	Accommodation and Catering, Associations & Youth groups – tent camps
Base area	31.70 m2
Width	5.28 m
Length	6.00 m
Eaves height	1.15 m
Ridge height	2.16 m