CLADIS
SERVING THE RESPONSE COMMUNITY

AZF 33 self-erecting tents with fully inflatable frame

Product Images

Short Description

Ready to use within minutes, the AZF series is the ideal solution for all emergency situations. Durable, they can be efficiently deployed on any type of terrain.

Description

Frame

Main beams and ridge beams are inflatable, made of airtight double-sided PVC-coated polyester fabric (1.10 kg/m²), and fixed to the cover and floor. Eaves purlins are made of aluminium. Easy replacement of cover and frame. The tents can be set up in 4-7 minutes, depending on the tent size. A pressure relief valve prevents excessive pressure in the frame.

Tent skin

Tent skin is made of double-sided PVC-coated polyester fabric (0.75 kg/m²); flame resistant, waterproof and mildew resistant.

Floor

Floor covering of double-sided PVC-coated polyester fabric (0.75 kg/m²). Available with non-slip embossing as an option (0.85 kg/m²).
Other colours are available on request.

Options and accessories

- Partition walls, inner liner and sunroof
- Protection groundsheet
- Additional side entrances
- Entrance modules
- Outer frame for additional snow load
- Connection modules tent-to-tent/ vehicule-container
- Hard plastic flooring
- Electric inflator
- Automatic pressure maintenance systems
- Lighting
- Power distributor/switchboards
- Heating/Air conditioning
- Lettering/branding

Additional Information

Application area	Civil Defence, Triage, Field Hospitals, First Aid Posts, Decontamination and Hazardous Goods Operations, Police/Gendarmerie, Weatherproof Shelter for Sensitive Equipment and Workshops, United Nations, NGOs/Humanitarian organizations
Base area	31.00 m²
Width	6.00 m
Length	5.15 m
Eaves height	2.35 m
Ridge height	3.04 m
Operating pressure	0.30 bar
Weight	160.00 kg